

BME ACTIVECORE™

Glass Door Chiller

Display / Bottom Mount

A new glass door chiller combining SKOPE's revolutionary new ActiveCore technology with a modern frameless aesthetic design. These models provide market leading energy savings along with new features to deliver optimal performance, efficiency and reliability.

Options

Available in 1 and 2 door models
Additional shelves
Illuminated sign panel

SIGNIFICANT ENERGY SAVINGS

Uses 35% less energy than the previous B1200G-2 model, saving more than \$266 per year*

Significantly reduced noise and improved quality, for quieter operation

Patented easy to install shelf clip and numbered shelf support strip, reduces set up time and enables finer adjustments

A frameless glass door design with aluminium trim

Redesigned kick panel for branding opportunities and easy access to filter for maintenance

Fitted with lock tabs for extra security

Optimal airflow and cooling performance reduces temperature variations and energy consumption

Split shelving system for improved product presentation

Premium energy efficient glass using a new low-emissivity, high performance coating technology, ideal for high humidity environments

Ergonomically designed, brushed stainless steel handles

New slotted back panel design allows chilled airflow to be pushed directly on the product

Updated controller with manual light switch

Revolutionary ActiveCore refrigeration system



Available in white only



Warranty
2 year protection



High Energy
Efficiency





ActiveCore™

Specifications

SKOPE®


BME ActiveCore™



Display / Bottom Mount



Integral front elevation


BME600-A - GLASS DOOR

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	Gross Volume 584 litres Total Shelf Area 1.62m ² Floor Area 0.62m ² (inc. 50mm stand-off)	 BME600-A 1 DOOR
BME600-A	185	Integral	Chiller		
		Integral External (mm)	Internal (mm)		
Height	2013	1454			
Width	740	640			
Depth**	843	602			
Door Height	1536				
Glass Area	0.92m ²				
<ul style="list-style-type: none"> • 4.35 MEPS (kWh/24h/m²) • Maximum height 2207mm with optional sign panel fitted • +1°C to +4°C in 43°C ambient 					



Integral front elevation

BME1200-A - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	Gross Volume 1079 litres Total Shelf Area 3.00m ² Floor Area 1.08m ² (inc. 50mm stand-off)	 BME1200-A 2 DOOR
BME1200-A	245	Integral	Chiller		
		Integral External (mm)	Internal (mm)		
Height	2013	1454			
Width	1280	1180			
Depth**	843	602			
Door Height	1536				
Glass Area	1.57 m ²				
<ul style="list-style-type: none"> • 3.86 MEPS (kWh/24h/m²) • Maximum height 2207mm with optional sign panel fitted • +1°C to +4°C in 43°C ambient 					

*Based on 30 cents per kW. Calculated using 4.55 kWh/24h(TEC) no illuminated sign panel.

**Total depth includes 50mm stand-off and 35mm handles. Cabinet depth of 758mm excludes stand-off and handles.