



Vacuum packing machine SU-810 LL 220/60/3



TECHNICAL SPECIFICATIONS

Pump capacity: 100 m³/h
Bar length: 848 mm + 848 mm
Total loading: 2200 W
Vacuum pressure (maximum): 0.5 mbar

Electrical supply: -- V / -- Hz / -- ~ (-- A)

Internal dimensions

·Width: 864 mm
·Depth: 603 mm
·Height: 215 mm

External dimensions (WxDxH)

·Width: 960 mm
·Depth: 757 mm
·Height: 998 mm

Net weight: 250 Kg
Noise level (1m.): 75 dB(A)
Background noise: 32 dB(A)

DEFAULT EQUIPMENT

- BUSCH pump.
- Sensor Controls.
- 25 programmable settings.
- Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- Soft air function.
- Clear methacrylate lid.
- "PAUSE" function.
- Liquid detection system.

OPTIONAL EQUIPMENT

- Vacuum packing pouches
- Vac-Norm external vacuum kit, containers and accessories
- Bag cutting kit
- Support for liquids
- Additional filling plates



Vacuum packing machine SU-810 LL 220/60/3

FLOORSTANDING UNIT. 100M³/H. 848+848 MM.

**Two sealing bars (848+848 mm.)
100 m³/h Busch vacuum pump.
Vacuum controlled by sensor.**

- Powered by Busch.
- Vacuum controlled by sensor.
- Vacuum PLUS.
- LCD colour screen: all information at a glance.
- Backlit touch keyboard.
- Programmable: 25-programme memory. Blocking option.
- "Pause" button.
- Phased vacuum programme.
- Detection of the evaporation of liquids.
- Double seal.
- Cordless sealing bar.
- Progressive decompression.
- Vac-Norm ready with Automatic decompression.
- Stainless steel body and chamber.
- Damped transparent lid of high durability polycarbonate.
- Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- Safety system with protection against vacuum failure.
- NSF-listed.



ER-4437/196 UNE-EN ISO 9001

SAMMIC, S.L.
Basarte, 1 - 20720 AZKOITIA
www.sammic.com

