

Vacuum packing machine SU-810GP 230-400/50/3N



SPECIFICATIONS SHEET

Pump capacity: 100 m³/h
 Bar length: 530 mm + 848 mm
 Total loading: 2200 W
 Vacuum pressure (maximum): 0.5 mbar

Electrical supply: 230 V-[v:002_tension2] / 50 Hz / 3 ~ (15.1 A)

Internal dimensions

·Width: 864 mm
 ·Depth: 603 mm
 ·Height: 215 mm

External dimensions (WxDxH)

·Width: 960 mm
 ·Depth: 757 mm
 ·Height: 998 mm

Net weight: 250 Kg
 Noise level (1m.): 75 dB(A)
 Background noise: 32 dB(A)

DEFAULT EQUIPMENT

- BUSCH pump.
- Sensor Controls.
- 25 programmable settings.
- Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- Soft air function.
- Clear methacrylate lid.
- "PAUSE" function.
- Liquid detection system.

OPTIONAL EQUIPMENT

- Inert gas
- Sealing plus
- Printer
- Vacuum packing bags
- External vacuum kit for Vac-Norm, containers and accessories
- Bag cutting kit
- Support for liquid packaging



Vacuum packing machine SU-810GP 230-400/50/3N

FLOORSTANDING UNIT. 100M³/H. 530+848 MM.

**Two sealing bars (530+848 mm.)
100 m³/h Busch vacuum pump.
Vacuum controlled by sensor.**

- Powered by Busch.
- Vacuum controlled by sensor.
- Vacuum PLUS.
- LCD colour screen: all information at a glance.
- Backlit touch keyboard.
- Programmable: 25-programme memory. Blocking option.
- "Pause" button.
- Phased vacuum programme.
- Detection of the evaporation of liquids.
- Double seal.
- Cordless sealing bar.
- Progressive decompression.
- Vac-Norm ready with Automatic decompression.
- Stainless steel body and chamber.
- Damped transparent lid of high durability polycarbonate.
- Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- Safety system with protection against vacuum failure.
- NSF-listed.