



Proveno 4G Electric Combi Jacketed Kettle Proveno 4G Combi 40E (4224300)

Standard Features

- Proveno kettle with integrated mixer
- Electric heated version
- Stepless mixing speed 15-140 rpm/min, auto-reverse
- Elevated control pillar with guiding touch panel
- Safety grid lid
- · Audiovisual signals for user
- Multi-function timer
- ProTemp real time temperature control, food and jacket temperature separately controlled
- Delta T cooking temperature of jacket rises accordingly when food temperature rises
- Programming on screen, unlimited number of programs and program phases, favourite pages, wash programs
- Automatic measured water filling
- Electric tilting tilting height 600mm
- Tilting while mixing function
- Auto tilt-back
- Measuring stick
- Retractable handshower
- Strainer plate
- USB Port on control panel
- Diagnostics for maintenance
- Unit shown includes free standing floor kit other options available

Please refer to Moffat price list for options and accessories


Flectrical

Total Heat


Load

Waste

Nett Weight







L

mm

870

Μ

mm

1055

U

mm

860

Т

mm

400

Door

mm

800

Technical Data

Net Volume Spare Volume Gross Volume	8 L
Dimensions Width Height Depth	1047mm 1535mm 706mm
Connections	
Water	Cold ø15mm Hot ø15mm

Power 12.5 KW
Voltage 400-415
3P+N+E 50/60H
AMP 25A
12.5kW
1210111

Latent 0.4 kW Sensible 2.4 kW By kitchen

contractor

200 kg

ower 12.5 kW
oltage 400-415V,
P+N+E 50/60Hz
MP 254

er 12.5 kW	
ge 400-415V, N+E 50/60Hz	4
25A	

12.J KVV
ltage 400-415V,
P+N+E 50/60Hz
/IP 25A
5kW

5V, Hz	40E	597	1740
	Model	mm	mm
		L1	Н



PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au

