

**MODEL: UBS6240**

HEIGHT: 900mm

WIDTH: 2400mm

DEPTH: 660mm

AMPERAGE: RA 4.37AMPS

START UP CURRENT: LRA 20.17 AMPS

MAX OPERATING AMPS: 6.56 AMPS

COOLING CAPACITY: 781w

TOTAL HEAT REJECTION: 1167w

ELECTRICAL SUPPLY: 230V – 50Hz

SET POINT TEMPERATURE: 3°C

MASS: 175 Kg

DRIER: 25g

GAS TYPE: R134A

GAS CHARGE: 300 g

CLASS: TROPICAL

CAP TUBE LENGTH: 1120mm

CAP TUBE SIZE: 061

COMPRESSOR: FF112HBX

NOISE LEVEL: 64dB

CONDENSOR: CD / 320 - 3R

EVAPORATOR COIL: EV / 290 – 3R

EVAPORATOR FAN: 10W

CONDENSOR FAN: 16W

FAN BLADE CONDENSOR: 250MM – 34°

CONTROLLER DIXELL CX02C

EVAPORATION: HOT PIPE

FOAM TYPE: ECOMATE

INSULATION: 33 DV

VOLUME: 859 LITRES

GASKET SIZE FULL DOOR: 547 X 667mm

GASKET SIZE HALF DOOR: 547 X 307mm

EVAPORATING TEMPERATURE: - 5°C

CONDENSING TEMPERATURE: 45.4°C

AMBIENT TEMPERATURE: 32°C



**WA DEALER  
PRACTICAL PRODUCTS PTY LTD**

PH: 08 9302 1299  
51 Paramount Dr Wangara WA 6065  
sales@practicalproducts.com.au  
www.practicalproducts.com.au

