



# ELECTRIC TILTING BRATT PAN 1200mm

E580-12, E580-12E

- 120L full stainless steel pan
- Manually operated tilting mechanism
- Optional electric power tilting mechanism
- Heavy-duty lid and hinge system
- Galvanized steel chassis
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular



## **Overall Construction**

- Heavy-duty galvanized steel chassis
- Side panels 1.2mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Front panels 0.9mm 304 stainless steel
- Vitreous enamelled pan front cover
- Full stainless steel pan with 2.0mm pan body
- 12mm thick stainless steel even heat pan base
- Large capacity pouring spout
- Heavy-duty spring balanced lid hinge system
- 1.5mm 304 stainless steel lid suitable as bench-top workspace
- Full width stainless steel lid handle
- Manually operated pan lift handwheel with fold-away handle
- Electrically powered pan tilting option
- 63mm dia. heavy-duty stainless steel legs with adjustable feet

### Controls

- Large easy use control knobs heat resistant reinforced
- Easy view control settings on knobs
- Single control knob for power and heating control
- Indicator lights for power and heating
- Quarter turn water valve control for ease of use
- 50-320°C thermostatic control
- Over temperature safety cut-out
- Fold away handle on manual pan tilt
- Pan up and down switches on electric pan tilt

# **Cleaning and Servicing**

- Seamless full stainless steel pan with rounded corners
- Easy clean stainless steel exterior panels
- Easy connection access via front service panels
- Service friendly lid hinge system
- Access to all parts from front of unit







# ELECTRIC TILTING BRATT PAN 1200mm

E580-12, E580-12E

#### **Specifications**

#### Elements

 $3 \times 5.66 kw$  stainless steel sheathed heating elements clad to pan base

# Electrical requirements

17kW

400-415Vac, 50/60hz, 3P+N+E

#### Phase loading

L1 23A L2 23A L3 23A

#### Par

Cooking surface 1080mm x 450mm, 4860cm2 215mm deep

#### Water connection

Cold water connection 1/2" tube connection via 15mm crox fitting 550kpa, 80psi max water pressure

#### **Dimensions**

Width 1200mm Depth 812mm Height 915mm Incl. splashback 1085mm With lid open 1566mm

## Nett weight

220kg


#### Packing data

1.36m3, 300kg Width 1245mm Depth 870mm Height 1255mm

#### Options

Joining caps


#### E580-12



#### E580-12E



#### E580-12, E580-12E



# WA DEALER PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au

