





Blue Seal Gas Combi Steamer SAPIENS RELOADED G10RSDW 10 x 1/1 GN



- Manual controls
- Multi-point core temperature probe
- Variable fan speed with up to 6 speeds
- 95 preset recipe programs, including programs for rehearing on the plate / pan
- 99 free programs, up to 9 cycles with name and icon creation
- AUTOCLIMA automatic system for measuring and controlling the humidity in the cooking chamber
- Fast-Dry, quick dehumidification of the cooking chamber
- LED HVS alphanumeric display for temperature, Autoclima, time and core temperature
- 2.4" LCD TFT colour display for favourite programs, preset programs, fan, automatic washing, menus and settings.
- Rapid selection scroller knob for program using scroll & push functions
- LED bars to indication actual cooking cycles in program mode
- Manual pre-heating
- Electronic thermostat 30°C-300°C
- Auto reverse (automatic reversing fan rotation) for perfect cooking uniformity
- Automatically regulated steam condensation
- Manual chamber pressure relief control
- Manual humidifier
- ECOVAPOR automatic control of the system saturation in the cooking chamber
- ECOSPEED oven optimises and controls the delivery of energy to maintain correct cooking temperature
- GREEN FINE TUNING burner modulation system with high efficiency exchanger to prevent power wastage and reduce harmful emissions
- Automatic LCS (Liquid Clean System) with built-in tank and automatic dispensing
- Built-in retractable hand shower with tap
- USB connection to download HACCP data, software updates and storing cooking programs

OPTIONAL FEATURES

- Right hinged door
- Configuration for connection to extraction hood

GENERAL FEATURES

- Direct Steam injection system
- Perfectly smooth, water tight chamber
- Double tempered glass door with air chamber and interior heat-reflecting glass reduces head radiation towards operator
- Hinged inner glass for easy cleaning
- Adjustable door hinge for optimal seal
- Fan motor thermic protection
- Low water alarm
- Component cooling system with overhear display control
- Self-diagnosis and fault display
- Oven light
- IPX5 spray-proof and hose proof







ECOVAPOR











FAST-DRY



Sapiens reloaded

OBLUE SERL

Blue Seal Gas Combi Steamer SAPIENS RELOADED G10RSDW 10 x 1/1 GN

Dimensions

Width 930mm Depth 825mm Height 1040mm Weight 180kg

Packed dimensions

Width 1000mm Depth 990mm Height 1250mm Weight 205kg

Shelves

1/1 GN 10 Shelf Spacings 70mm

Installation requirements

(for precise installation instructions, please refer to the unit's installation manual).

Power connection requirements

230-240V, 50Hz, 1P+N+E
Supply line voltage 1.0kW
Electrical power 0A
Rated current 3 pin plug
(10A) cordset fitted

Gas connection

Nominal gas consumption 64.8MJ/hr

Gas connection size R1

Exhaust connection to ventilation system with safety

Observe regulations for gas suppliers.

Installation clearances

- rear 25mm - right 500mm*
- left 50mr *Clearance required on

*Clearance required on fixed installations for service accessibility.

If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 400mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible

Water connection

- requirements
 Cold water
- Flow pressure (200-500kPa)
- Soft water connection*
- Shut-off valve with return flow inhibitor and dirt filter
- Water supply R3/4
- R50 waste water connection

(*Water softener may be required. Please refer to installation manual for water treatment values.)













