

# EVO 40ST



Stoddart Manufacturing are proud to present the Culinaire range of glasswashers.

These glasswashers have been engineered to meet harsh Australian conditions.

The Culinaire range of glasswashers offer the latest in smart one-touch operation for ease of use as well as maintaining low water and low energy consumption.

All Culinaire glasswashers are covered with one of the best warranty's in Australia for machines in their price range.

### **High Performance**

- 5 wash cycles to meet demands (1, 2, 3, 4 & 10 minutes)
- Solid stainless steel door hinges with no plastic
- Robust double skin insulated door
- Low water consumption of only 2 litres per cycle
- Upper and lower wash and rinse arms with strong mechanical action allows for washing of coffee mugs, saucers and other lightly soiled items
- Electronic interface with enhanced functionality
- Service diagnostics for error notification
- Soft start to protect glassware
- Self cleaning cycle
- Automatic drain cycle
- Precise temperature readout and display
- Automatic detergent and rinse-aid injection
- Automatic drain pump
- Plug and play installation
- Braided stainless steel water supply hose
- Drain pump outlet waste hose
- I5 amp plug and lead set
- Dual chemical injector lines
- No commissioning required

OPTIONAL ACCESSORIES

867060 Insert for 14 saucers 867062 Insert for 7 plates

CMGE.0573 Additional 14" x 17" baskets

**CNCL.0072** "Masterglass" commercial glasswashing detergent

CNCL.0070 "Hi-Tech" commercial glasswashing detergent


**CNCL.0071** "Glisten" sparkling finish rinse-aid

CNCL.0073 "Phos Kleen" professional descaling solution







## EVO 40ST



#### **FRONT VIEW**





We distribute and recommend:











MODEL	EVO40ST
Dimension (W x D x H)	480mm x 505mm x 750mm
Rack type	14"x 14"& 14"x 17"
Cycle	1, 2, 3, 4 & 10 minute cycles
Wash pump power	0.5HP - 0.37 kW
Boiler/Booster power	2.8 kW
Wash tank element	2.0 kW
Power supply	Single phase, 240 volt, 50 Hz
Total installed load	14.5 Amp
Water consumption	2.0 litre per cycle
Soft start & self cleaning	YES
HACCP temp readouts	YES
Smart self diagnostics	YES
Automatic drain pump	YES
Braided water supply line	YES
350 kpa pressure reduction valve	YES
Washing temperature	60°C
Rinsing temperature	85°C
17" x 14" basket	YES
Drain outlet hose	YES
Dual chemical pumps	YES
Dual chemical hoses	YES
Castors and adjustable feet	YES
Waste connection	1.5 BSP
Water inlet pressure	200 kpa minimum
Water supply temperature	50°C
Water connection	3/4"
Refer to the user manual for complete installation instructions	

Dealer:

#### WA DEALER PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au

