

ELEVATION SERIES CUBE ICE MAKER CIMO325




Model: □ CIMO325



Features and Benefits

- 22.25" (565 mm) wide space-saving design.
- Produces up to 132 kg of ice perday.
- Energy and Environment
 - Exceeds new 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.
- Sanitation
 - -Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
 - -Built in Agion[®] ensures unbeatable antimicrobial protection.
 - -Smart LED light indicates machine status and when cleaning is required.
 - Simple, one-touch controls for sanitization and descaling. -BPA-free snap-in, snap-out dishwasher-safe components.
- · Unique Dual Exhaust Air-cooled machines are designed to discharge hot air from both the side and top of the unit, increasing installation flexibility and reducing the potential of obstructed exhaust.
- Universal Smart Harness[™] control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

Ice Form



Biı	n Chart	Kits for	Combining W	/ider Bin	s with Small	ler Models				
	ICE STORAGE BINS									
	Model No. Capacity Width	B25 110 kg 762 mm	10 kg 560 mm	B40 156 kg 762 mm	B42 160 kg 559 mm	180 kg 760 mm	B55 232 kg 762 mm	ICB230SC 232 kg 764 mm	CIB400 400 kg 1,220 mm	B110 388 kg 1,219 mm
Kits	CIM0325	BT55	Kit Not	BT55	Kit Not		BT55		Ň	A

Required



(NSE)

Ice-O-Matic

*See Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

Options & Accessories

WATER FILTERS								
Ice Machine Model	Manifold							
	System	Replacement						
CIM0325	CD20B	CD200B						

C E agion

Note: All modular cube CIM units can be installed with the O_z-Matic[™] Ozone Delivery System.

Ice Maker Warranty

COMMERCIAL WARRANTY					
Ice Maker	3 YEARS parts and labor				
Evaporator and Compressor	5 YEARS parts				



PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au



Required






ELEVATION SERIES CUBE ICE MAKER CIMO325

Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".



Dual Exhaust for Installation Flexibility



Operating Requirements

	MINIMUM	MAXIMUM		
		50Hz		
Ambient Temp. Range Air	10°C			
Water Temp.	4.4°C	43°C		
Water Pressure	1.4 BAR	5.5 BAR		

Dimensions

ALL MODELS								
W x D x H (mm)	565 x 616 x 540							

Specifications

		Half-Cube Ice Production per 24hrs		Water Usage litres per 45 kg of Ice 32°c air/21°c water		kWH Used	Watts Used				Refrigeration
Model Number	Cond. Unit	21°c air/ 10°c water (kg)	32°c air/ 21°c water (kg)	Potable	Condenser	per 45 kg of ice @ 32°c air/ 21°c water	Per Hr @ 32°c air/ 21°c water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Refrigeration Capacity per hour
CIM0325A	Air	132	100	83	-	7.32	677	220-240/50/1	6.9	16	1,290

* Daily ice production based on half cube configuration.

Notes: Number of Wires: Approx. Shipping Weight kg: Refrigerant Type:

3 (including ground) CIMO325A 68 R4O4A



PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au