

IDT0450A IYT0450A

INDIGO NXT

50Hz iT0450 Ice Cube Machine

IDT0450W





Indigo NXT Series iT0450 Ice Machine on D400 Bin

Ice Machine Electric

230/ 50/ 1

Models

Minimum circuit ampacity:

Air-cooled: 5.6 amps Water-cooled: 5.3 amps

Maximum fuse size:

Air Cooled: 15 amps Water cooled 15 amps

Specifications

BTU Per Hour:

3,800 (average), and 6,000 (peak)

Refrigerant:

R410A CFS - Free Lowers global warming by 48%

Operating Limits:

- Ambient Temperature Range: 40° to 110° F (4.4° to 43.3° C)
 Water Temperature Range: 40° to 90° F (4.4° to 32.2° C)
- Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo NXT Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- New levels of Performance Showcasing an average of 9% lower energy consumption, up to 12% increase in ice production and a 19% reduction in condenser water usage and a 5% reduction in potable water usage. . This translates into lower cost of ownership over the life of your machine.
- easyTouch® Display New icon based touch screen takes the guess work out of owning and operating an ice machine.
- Multiple Language Capability The easyTouch display is available in multiple languages selected in the initial start-up installation Wizard.
- Programmable Ice Production Now its super easy to program your ice machine to be off at certain times of the day to save money with fluctuating electrical rates. Also programmable by daily ice production volume.
- Easy to Clean Foodzone Hinge front door swing out for easy access. Removable water-trough, distribution tube, curtain, water probe and water pump for fast and efficient cleaning. Selected components are made with AlphaSan® antimicrobial.
- Intelligent Diagnostics Provides 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe Unique patented technology allows for reliable operation in challenging water conditions and environments
- **DuraTech® Exterior** Provides superior corrosion resistant above stainless steel. Innovative clear-coat resists fingerprints and dirt making it easier to keep clean.
- Available LuminIce® II Growth Inhibitor Controls the growth of bacteria and yeast within the Food zone keeping the machine cleaner longer. A new indicator in the display keeps you abreast of the operational status.



Ice Shape



Half Dice %" x 1%" x 7%" (.95 x 2.86 x 2.22 cm) Cube weight 5.7 g



Dice%" x %" x %"
(2.22 x 2.22 x 2.22 cm)
Cube weight 8.5 g









COMPANY WITH QUALITY SYSTEM





MANITOWOC*



21.50" (54.61 cm)

32.00" (81.28 cm)

24.00" (60.96 cm)

2.47" (6.27 cm)

115/60/1

50Hz



iT0450 on D-400 Storage Bin

- A Electrical Entrance (2) Options
- B 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units)
- (vater-cooled units)
- 1/2" (1.27 cm) Auxillary Base Drain Socket
- (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
- F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain
- © 3/4" (1.91 cm) Bin Drain



Installation Note Minimum installation clearance:

Top/side: 12" (30.50

cm)Back is 5" (12.7 cm)

11.00" (27.94 cm) 30.00" (76.20 cm) 34.00" (86.36 cm)

1.75" (4.45 cm) 4.00" (10.16 cm)

5.25" (13.34 cr

Space-Saving Design





| | iT0450 D-400 | iT0450 D-570 | |
|----------------|------------------------|------------------------|--|
| Height | 59.50" 151.13 cm | | |
| Width | 30.00" 76.2 cm | 30.00" 76.2 cm | |
| Depth | 34.00" 86.30 cm | 34.00" 86.30 cm | |
| Bin Storage | 365 lbs. 165.7 kgs. | 543 lbs. 241.1 kgs. | |

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm). Bin capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice.

Specifications

| | | | Ice Production 24 Hours | | Power Usage kWh 45.4 kg / 100 lbs @ 32°Air / 21°C Water 90°Air / 70°F Water | Potable Water |
|-------|--|--------------|--|---|--|------------------------------------|
| | Model | Ice Shape | 21°Air /10°C Water 70°Air/ 50°F Water | 32°Air / 21°C Water 90°Air/ 70°F Water | 1 Ph | Usage/100 lbs. 45.4 kgs. of Ice |
| AIR | IDT0450A di | dice | 440 lbs. | 355 lbs. | 5.30 | 19 Gal. |
| | | | 200 kgs | 161 kgs | | 71.9 L |
| | IYT0450A half-dice | 460 lbs. | 375 lbs. | 5.20 | 19 Gal. | |
| | | 100 | 209 kgs | 170 kgs | 5.20 | 71.9 L |
| #.C | IDT0450W dice | dice | 420 lbs. | 355 lbs. | 4.88 | 19 Gal. |
| | | | 191 kgs | 161 kgs | | 71.9 L |
| WATER | * Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 140 gal/ 530 L. | | | | | |

* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 140 gal/ 530 L.

Order separately: Ice storage bin for all units

This product is hermetically sealed and contains fluorinated greenhouse gas R404A

Accessories

LuminIce® II **Growth Inhibitor**

reduces yeast and bacteria growth for a cleaner ice machine.



External Scoop holder

Protect the ice scoop with the NSF approved versatile scoop holder.



Arctic Pure® Water Filters

Reduces sediment and chlorine odors for better tasting ice.



5645 06/18

Welbilt reserves the right to make changes to the design or specifications without prior notice.

