



Merrychef Advanced High Speed Cook Oven

cikon e5 HP



Standard Features


- Oven cavity to suit up to gastronorm 2/3 GN tray size
- 2 rack positions
- Up to 5 times faster than a convection oven
- Advanced Cooking Technology® combines two heat technologies: microwave and convection heat
- Ventless cooking capabilities through built in catalytic converter
- Colour easyTouch® icon driven touch screen control panel with the capability of storing up to 1,024 multi-stage recipe programs
- Each program offers up to six (6) stages with programmable cooking times, microwave power setting and user instructions for each stage
- Easy menu updates or data transfer via USB
- MenuConnectTM ethernet connection for remote menu updating and diagnostics
- Precise temperature setting range from 100°C 275°C
- Self-diagnostics capability to monitor components
- · Cool to touch door exterior
- Stainless steel construction
- · Easy to clean interior
- · Easy access to front facing air filter
- Multi-languages available

Includes

- Cool down pan
- · Wire rack
- Oven tray x 2
- Cleaning care package, consisting of:
 - 1x oven cleaner (bottle)
 - 1x oven protector (bottle)

Accessories

- Cook plate liners
- Paddles
- Trays
- Racks
- Handles



Airflow (top view)


The convection fan (1) draws air from the oven cavity, circulating it over the heating elements (2) to obtain the set temperature and through the catalytic converter (3)* to clean the air before returning it to the oven cavity.






Merrychef Advanced High Speed Cook Oven

©ikon° e5 HP





MICROWAVE POWER

Microwave settings, off or 5-100% in 1% increments Distribution system, rotating active antennae

CONVECTED HEAT

Temperature settings off and from 100°C to 275°C in 1°C steps

Distribution system, tuned impingement

DIMENSIONS

| Width | 711 mm |
|--------|---------|
| Depth | 643 mm |
| Height | 644 mm |
| Weight | 92.5 kg |
| | |

PACKED DIMENSIONS

Width 770 mm
Depth 860 mm
Height 940 mm
Weight (including cleaning system) 118 kg

INSTALLATION REQUIREMENTS

 Rear
 50 mm

 Right
 50 mm

 Left
 50 mm

INSTALLATION REQUIREMENTS

For precise installation instructions please refer to the units installation manual

ELECTRICAL SUPPLY

400-415V, 50Hz (2P+N+E)
Rated power consumption 6.2 kW
Rated current 20A
20A 5 pin plug
All Merrychef ovens require installing a type D circuit breaker for all installations.

POWER OUTPUT (APPROX.)

 $\begin{tabular}{llll} Microwave & 1.4 kW \\ Convected heat & 3.2 kW \\ Combination mode & 1.4** + 3.2 kW \\ **This is approximate microwave power output. \\ \end{tabular}$

WA DEALER
PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299
51 Paramount Dr Wangara WA 6065
sales@practicalproducts.com.au
www.practicalproducts.com.au