



## AF Series Self Contained Flake Ice Machine - up to 120kg AF 103 AS OX Flake Ice



Flake ice



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 120kg daily production rate
- 30kg storage bin capacity
- Air cooled version
- XSafe Natural Sanitation System
- Stainless steel auger and freezing cylinder evaporator
- Water in / ice out concept limits excess energy, water and time wastage
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electromechanic controls
- Clean alert indicator to clean filter
- Resistant stainless steel exterior
- Easy access front condenser air filter
- External indicator lights to show operation status
- Includes removable air filter, ice scoop, water and drain hose


























# AF Series Self Contained Flake Ice Machine - up to 120kg


### **AF 103 AS OX**








AIR FLOW



UNIT OF MEASUREMENT: mm

- 1. 13/16" OD OVERFLOW DRAIN
- 2. 3/4"- WATER INLET
- 3. 3/4"- WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4"- WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET



#### Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
120	120	93

Dimensions

Width: 592mm Depth: 622mm

Height: 1078mm (including legs)

Nett weight: 66kg Packed weight: 74kg

#### Water consumption

Air cooled version: 4.2 litres per hour

#### Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 550W,

10A cordset supplied

No. Circuit wire: 3 Compressor: 1200W Energy consumption: 11.5kWh/24hr

Refrigerant type

R404A

#### Installation distance from wall

Rear 100mm

Operating requirement air temperature 10-43°C

#### Water connection requirements

Inlet connection: R ¾"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: ؾ"

