



EC Series Self Contained Gourmet Ice Machines — with Progressive Water Discharge — up to 51kg

ECM 107 AS OX Medium gourmet cube 20g, Ø30mm x 34mm



Medium gourmet cube 20g, 30mm dia x H 34mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 51kg daily production rate
- 23kg storage bin capacity
- Air cooled version
- Produces individual transparent Gourmet crystal clear supercubes
- Hydrocarbons R290 refrigerant gas
- XSafe Natural Sanitation System
- PWD-Progressive water discharge: pumps excess residual water up to a distance up to 15 meters
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electromechanic controls
- Horizontal ice evaporator spray-system technology
- · Resistant stainless steel exterior
- Front access condenser air filter, removable and washable

- Routine maintenance visible alarm light on front panel
- Ergonomically designed ice storage access with disappearing door and door closing movement dampening system
- Includes removable air filter, ice scoop, water and drain hose
- Optional adjustable feet available up to 850mm high


















EC Series Self Contained Gourmet Ice Machines — with Progressive Water Discharge — up to 51kg

ECM 107 AS OX








UNIT OF MEASUREMENT: **mm**

- 1. 13/16" WATER OUTLET
- 2. 3/4" GAS WATER INLET WATER COOLED UNIT ONLY
- 3. 3/4" GAS WATER INLET
- 4. 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- 5. CORD SET



Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
53	51	43

Dimensions

Width: 531mm Depth: 600mm

Height: up to 850mm high optional

Nett weight: 49kg Packed weight: 56kg

Water consumption

Air cooled version: 5.2 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 580W,

10A cordset supplied

No. Circuit wire: 3 Compressor: 1215W Energy consumption: 10.7kW/hr

Refrigerant type

R290

Installation distance from wall

Rear 100mm Sides 150mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R ³/₄"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø³/₄"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.

© Copyright Moffat Ltd



PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au