



# NU Series Self Contained Dice Ice Machines – up to 45kg

**NU 100 AS OX** Dice cube 10g, 22mm x 22mm x 22mm **NUH 100 AS OX** Half dice cube 6g, 10mm x 22mm x 28mm



Dice cube 10 g W 22 x D 22 x H 22 mm



Half dice cube 6 g W 10 x D 22 x H 28 mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 45kg daily production rate
- 20kg storage bin capacity
- Air cooled version
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Vertical evaporator spray-system technology
- XSafe Natural Sanitation System
- Ergonomic access to ice with sliding disappearing door
- One touch cleaning for time and labour saving
- Resistant stainless steel exterior
- Easy access front condenser air filter
- Routine maintenance visible alarm light on front panel
- Includes removable air filter, ice scoop, water and drain hose

























# NU Series Self Contained Dice Ice Machines – up to 45kg

# **NU 100 AS OX, NUH 100 AS OX**









UNIT OF MEASUREMENT: mm

## Ice production per 24 hours

Ambient temperature / Water temperature

	10°C / 10°C	21°C / 10°C	32°C / 21°C
NU 100 AS OX	56	45	32
NUH 100 AS OX	50	45	32

#### Dimensions

Width: 600mm Depth: 610mm

Height: 770mm (including feet)

Nett weight: 50kg Packed weight: 60kg

#### Water consumption

Air cooled version: 3.2 litres per hour

# Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 450W,

10A cordset supplied

No. Circuit wire: 3 Compressor: 780W Energy consumption: 9.2kW/hr

## Refrigerant type

R404a

Installation distance from wall

Rear 100mm Sides 150mm

Operating requirement air temperature 10-43°C

## Water connection requirements

Inlet connection: R ¾"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: Ø ¾"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.

© Copyright Moffat Ltd



PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au