

# specifications




## SKT650N-A Series

ActiveCore Series, 1 Door (Glass), Upright Fridge

Project: \_\_\_\_\_

Item No: \_\_\_\_\_



CABINET			
Model ID	SKT650N-A	SKT650N-AC	SKT650N-ACX
Doors	1 × self-closing, reversible, double glazed, single Low-E, lockable, argon filled, toughened safety glass swing door (hinged RH)		
Internal door opening	1 × door openings: 1570mm high × 620mm wide		
Shelves	5 × adjustable height wire shelves: 625mm wide × 470mm deep		
Sign	Sign replacement panel	Illuminated sign	Illuminated sign
Material	Powdercoat galvanized steel or stainless steel interior & exterior		
PERFORMANCE			
Max. ambient temp.	40°C		
Temperature range	1°C to 4°C (adjustable via SKOPE-connect 1°C to 15°C)		
GEMS class	M1		
GEMS energy consumption	2.36 kWh/24h	2.46 kWh/24h	2.60 kWh/24h
GEMS annual running cost	\$259 p.a. (@ \$0.30/kWh)	\$270 p.a. (@ \$0.30/kWh)	\$285 p.a. (@ \$0.30/kWh)
ELECTRICAL			
Electrical safety climate class	5		
Interior side lighting	1 × 1400mm, 15W LED	1 × 1400mm, 15W LED	n.a.
Interior shelf lighting	n.a.	n.a.	5 × 605mm, 7W LED
Sign lighting	n.a.	1 × 670mm, 7W LED	1 × 670mm, 7W LED
Power cord	Supplied with 2.3m, 10 Amp plug and lead		
Power supply	220-240 Volts a.c. 50 Hz, single phase supply		
Current draw	2.9 Amps (includes unit 2.6 Amps)		
REFRIGERATION			
Controller	SCS Connect (SKOPE-connect™ compatible)		
Connectivity interface	Bluetooth® wireless technology		
Refrigeration system	Top mounted, integral, removable ActiveCore refrigeration unit (UTHCNI-0010)		
Refrigerant	R290 / 99g (natural refrigerant)		
Nominal capacity	740 Watts		
Heat rejection (Avg/peak)	100 Watts/140 Watts	105 Watts/150 Watts	110 Watts/180 Watts
Drainage	No plumbing required		

DIMENSIONS		
	External	Internal
Height	2200mm	1570mm
Width	740mm	640mm
Depth	745mm	554mm
Floor area	0.55m <sup>2</sup>	
Weight	170kg	
Gross volume	610L	

\* Depth 695mm excludes removable door handle and door lock bracket

Dimensional tolerances		
Before installing this cabinet allow the following dimensional tolerances:		
Linear dimensions	Overall cabinet dimensions	
Less than 1 metre	±5mm	
More than 1 metre	-5mm to +10mm	
	Length of multiple cabinets	
	At each joint	At each end wall
Less than 1 metre	±5mm	+15mm
More than 1 metre	-5mm to +10mm	+15mm

Ventilation requirements	
Top	300mm
Sides	Not required
Back	Not required
Bottom	Not required

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2018 SKOPE Industries Limited

WA DEALER  
PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299  
51 Paramount Dr Wangara WA 6065  
sales@practicalproducts.com.au  
www.practicalproducts.com.au

