

The Australian owned and designed\* Trueheat RC Series of Gas Cooking Equipment has been developed for the restaurant and cafe market with a high quality finish, designed to fulfill the busy demands within a commercial kitchen.

Powerful 24MJ/hr open burners with individual standing pilots included. 100% Flame failure controls included as standard. Matt finish Euro look cast iron trivets radiate heat and design makes it easy to move pots around the surface.

16mm thick steel griddle plate with 22.5MJ/hr burner per 300mm section.

Note: Griddle is convertible to left hand side. Additional charges apply.

DIMENSIONS & WE	EIGHT		
External Dimension:	600W x 803D x 45	55H mm	
Net Weight: 69kg			
Working height : 910	0mm (+/-15mm with	n stand)	
Combustible wall cle	earance: Side: 150	mm, Rear: 150m	m
TECHNICAL DATA			
Gas Type: Natural or Propane			
Total Output(MJ/hr):	Natural Gas 64.5	Propane Gas 64.5	
Burner Ratings (MJ/ Open Burner (MJ/hr) Griddle per 300mm:	): 24	Propane Gas 24 16.5	lgnition Type Manual Piezo
Gas Connection: ¾" Female			
AGA approval number: AGA 6652 G			
SHIPPING DATA			
Shipping Weight: 88	kg		
Shipping Dimension	s: 680W x 900D x	590H mm	
OPTIONAL ACCES	SORIES		
Part Number:	Description:		
RCSTD6	600mm Stand complete with shelf		
B05002	Adjustable leg for RCT countertop mounting		
	4 legs, 2 brackets, 6 screws (complete set for table top mounting)		
MS-CSTRB	Castor with brake to suit both 600mm and 900mm		
MS-CSTR	Castor without brake to suit both 600mm and 900mm		
	900mm ¾ flexible gas hose with quick connect fittings and restraint		
	1200mm ¾ flexible gas hose with quick connect fittings and restraint		
SPECIFICATIONS ARE SUBJE	CT TO CHANGE WITHOUT	NOTICE.	

Note: Stands fitted with castors will need to be cut down by 120-150mm.

\*manufactured in China

## WA DEALER PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au





<u>RC</u>T6-2-3G



Stand sold separately

PRACTICAL PRODUCTS





96 GIS CONNECTOR POINT 803 600

555 455 455 100 233.5 370 156.5 455