



Target Top Gas / Electric Static Oven Range **900mm**

RNLB8110GE



- Heavy-duty cast iron top with removable centre ring
- Matched modular height machined top for seamless work surface
- High output dual ring cast iron burner
- GN 2/1 6.5kW electric static oven
- Drop down door
- Stainless steel exterior
- Black vitreous enamel finish to front panels
- Easy clean
- Easy service
- Fully modular

OVERALL CONSTRUCTION

- Galvanized steel chassis
- Welded hob with 1.5mm 304 stainless steel bull nose
- Splashback and hob sides 1.2mm 304 stainless steel
- Front panels and oven sides 0.9mm 304 stainless steel
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet

TARGET TOP

- 3 piece heavy-duty cast iron top with fully machined surface
- Top plates and removable centre with integral spill protection design
- · Cast top reinforced with integral heat fins for heat zone definition
- 45MJ dual ring cast iron burner with single control
- Full pilot and flame failure protection
- 50mm thick refractory brick lined burner box for high heat retention
- Stainless steel spill tray
- · Supplied with heavy-duty centre casting removal tool
- OVEN
- Fully welded and vitreous enamelled oven liner
- GN 2/1 capacity with 4 position racking
- · Heavy-duty easy remove heavy wire chrome rack supports
- Cast iron even heat oven sole plate
- 6.5kW heating elements
- Welded frame drop down door with heavy-duty spring hinge system
- 0.9mm 304 stainless steel door outer
- 1.0mm press formed vitreous enamelled door inner
- High density fibreglass insulated
- Stay cool stainless steel door handle with cast metal handle mounts
- Supplied with two chrome wire oven racks

CONTROLS

- Large easy use control knob heat resistant reinforced
- Easy view control settings on knob

TARGET TOP

- Variable high to low burner control
- Single control knob for burner and pilot system
- Flame failure pilot burner
- Manual pilot ignition for reliable operation

OVEN

- · Separate temperature and top heat power regulation controls
- 50-320°C thermostatic control
- Lo-Hi top heat control
- Indicator lights for power and heating

CLEANING AND SERVICING

- Removable oven racking and sole plate
- · Easy clean vitreous enamel oven and door inner
- Easy clean stainless steel exterior
- Fully serviceable from front of unit
- Door hinge spring adjustable on unit (door outer removed)
- Door disengages for lift off removal and increased service access
- All parts front accessible from installed position


Series Options RNLB - Low back models RNB - 215mm splashback option





Target Top Gas / Electric Static Oven Range **900mm**

RNLB8110GE





SPECIFICATIONS Burners 45MJ dual ring cast iron - Target Top **Oven Elements** 4.5kW bottom heat element 2.0kW top heat element Gas power (gross) 45MJ/hr, 16.2kW Electrical requirements 6.5kW 1 phase connection: 230-240Vac, 50/60hz, 1P+N+E, 27A 3 phase connection: 400-415Vac, 50/60hz, 3P+N+E 1194A L2 9.4A L3 8.3A Target Top Cooking surface 900mm x 625mm, 5625cm2 Centre 280mm diameter Maximum plate temperature at centre 500°C **Oven Dimensions** Width 665mm Depth 590mm Height 385mm Rack size 660mm x 540mm Rack positions 4 Gas connection R ¾ (BSP) male 130mm from RH side, 32mm from rear, and 655mm from floor Optional underside connection (refer specification drawing) All units supplied with Natural and LP gas regulator

Electrical connection 23mm from RH side, 484mm from rear, and 150mm from floor Dimensions Width 900mm Depth 805mm Height 915mm Incl. low back 970mm Incl. splashback option 1130mm Nett weight 275kg Packing data 1.03m3, 340kg Width 945mm Depth 870mm Height 1255mm Gas types Available in Natural gas and LP gas Please specify when ordering Units supplied complete with gas type conversion kits Other gas types on request

OPTIONS AT EXTRA COST

Joining caps Castors Plinth mounting



PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au