

Technical data sheet for

ELECTRIC SALAMANDER

SN8200E





- Powerful 6kW infra-red elements
- Left and right heat control
- Branding plate option
- Wall mounting bracket
- Easy to clean
- Easy service

Overall Construction

- Monocoque construction
- $\bullet \ \ \text{External panels of 0.9mm 304 grade stainless steel}\\$
- Stainless steel tray under grilling area with grease trough
- Two 3kW infra-red elements

Racking

- Four position racking (flat or inclined)
- Adjustable chrome wire rack with heat resistant handles

Controls

- · Large easy use controls
- Heat resistant reinforced control knobs
- Indicator light for each element on
- Recessed front panels for hand and control protection
- Each side controlled by a 3 heat switch

Cleaning and Servicing

- Access to all parts from front of unit
- Stainless steel and vitreous porcelain enamel surfaces used throughout



Technical data sheet for



ELECTRIC SALAMANDER

Specifications Elements

2 x 3kW Electrical requirements 230-240V, 1P+N+E, 50/60Hz, 6kW, 25A

DIMENSIONS

Width 900mm Depth 424mm (455mm with wall mounting bracket) Height 456mm

COOKING AREA

Rack size 610mm x 310mm, 1890cm2 Branding Plate 610mm x 310mm, 1890cm2


NETT WEIGHT 36kg

PACKING DATA 0.31m3, 63kg Width 945mm Depth 520mm Height 635mm

ELECTRICAL CONNECTION
230-240V 1 phase hard wired via terminal block at back of unit 64mm from right side and 90mm from bottom of unit

OPTIONS AT EXTRA COST
100mm high feet for bench mounting
Branding kit - includes one double-sided,
ribbed cast aluminium branding plate

SN8200E



WA DEALER PRACTICAL PRODUCTS PTY LTD

PH: 08 9302 1299 51 Paramount Dr Wangara WA 6065 sales@practicalproducts.com.au www.practicalproducts.com.au